

# Hospital Push/Pull Latches



Innovation, Quality,  
Customer Service...

## LR6000 Series – Ligature-Resistant Cylindrical Latches

### Standard Features

- New ligature-resistant design provides a sleek look as well as functionality not commonly found in push/pull trim
- Cylindrical latch application – passage function
- 1-3/4" standard door thickness (specify if different)
- Meets ADA requirements
- Trim is mounted using four thru-bolts for maximum stability
- Non-handed for installation and stocking ease
- Trim can be mounted vertical or horizontal (with handles pointing toward hinge edge of door)
- UL Listed in U.S.A. and Canada for use on door fire rated 90 minutes or less, up to 4'0" x 8'0"
- LR trim also available for mortise lock bodies – LR6600 and LR6700 Series (See pages C-16 and C-20 for details)
- 1/2" Latch Bolt Throw
- Patent# 7,258,374 & Additional Patents Pending

**Optional "Q"**  
Quiet Latch available  
- Zero decibels gained  
when operating  
the handles.  
Patent(s) pending.



*Optional Custom Engraving Shown*

### How to Order:

**Example: LR6000 2 A – US32D – AM**

**Model:** \_\_\_\_\_

- LR6000

**Latch Backset:** \_\_\_\_\_

- 2 = 2-3/4"    • 5 = 5"
- 3 = 3-3/4"    • 7 = 7"

**Strike:** \_\_\_\_\_

- T = 2-3/4" T-Strike
- A = 4-7/8" ASA Strike

**Finish:** \_\_\_\_\_

- US32D    • US32    • US10B    • US3
- US26D    • US26    • US10    • US4

**Options, if Needed:** \_\_\_\_\_

- AM    • L    • PL    • PS    • SEC    • THICK    • P    • Q
- (See pages C-3 to C-5 for details)

