



345 Ball catch, adjustable

- Recommended for lower frequency opening applications
- Ideal for cabinets and small interior doors
- Free rolling ball insures smooth, positive and trouble-free action
- Adjustable threaded barrel compensates for various door clearances
- Adjustable spring tension
- Units packed with wood screws

Certifications

Meets ANSI/BHMA A156.9, B23013

Material substrate

Made from wrought brass

Dimensions

- Face plate: 3/4" wide x 1-1/2" high
- Bore: 1" deep x 9/16" diameter
- Strike: 25/32" wide x 1-1/2" high, lip to center- 13/32"

Finishes

ВНМА	Description	Substrate	Finish
605	Bright brass	Brass	US3
609	Blackened brass	Brass	US5
612	Satin bronze	Brass	US10
613	Oil rubbed bronze	Brass	US10B
619	Satin nickel	Brass	US15
625	Bright chrome	Brass	US26
626	Satin chrome	Brass	US26D

For other colors, consult factory.





347 Ball catch, dual adjustable - square corners

- Recommended for lower frequency opening applications
- Ideal for cabinets and small interior doors
- Free rolling ball insures smooth, positive and trouble-free action
- Adjustable threaded barrel compensates for various door clearances
- Adjustable spring tension
- Rounded corners on strike lip for safety
- Units packed with wood screws

Certifications

Meets ANSI/BHMA A156.9, B23013

Material substrate

Made from wrought brass

Dimensions

- Face Plate: 1" wide x 2-1/8" high
- Bore: 7/8" diameter x 1-3/8" deep
- Strike: 1-3/8" wide x 2-1/8" high, lip to center- 7/8"

Finishes

BHMA	Description	Substrate	Finish
605	Bright brass	Brass	US3
606	Satin brass	Brass	US3
609	Blackened brass	Brass	US5
612	Satin bronze	Brass	US10
613	Oil rubbed bronze	Brass	US10B
619	Satin nickel	Brass	US15
625	Bright chrome	Brass	US26
626	Satin chrome	Brass	US26D
643e/716	Aged bronze	Brass	643e/716
622	Matte black	Brass	BLK

For other colors, consult factory.