



CL21 Ball catch

- Four-way catch with hexagon stud
- Ideal for holding medium duty doors
- The strike slides between two stainless steel balls that are under spring tension. As the strike engages, the door is held tightly shut
- Strike can enter body from any direction
- Spring tension is easily adjusted to suit field conditions
- Body can be surface applied or mortised
- Units packed with wood screws

Certifications

- Meets ANSI/BHMA A156.9

Material substrate

- Made from brass

Available accessory items

- Security pin screws

Dimensions

- Body: 3/4" wide x 3" high x 3/4" deep
- Strike: 3/4" wide hex x 1-1/2" high

Finishes

BHMA	Description	Substrate	Finish
626	Satin chrome	Brass	US26D

For other colors, consult factory.



CL21A Ball catch

- Four-way catch with plate type strike
- Ideal for closet doors, access doors, hinged openings and numerous other applications
- The strike slides between two stainless steel balls that are under spring tension. As the strike engages, the door is held tightly shut
- Strike can enter body from any direction
- Spring tension is easily adjusted to suit field conditions
- Body can be surface applied or mortised
- Units packed with wood screws

Certifications

- Meets ANSI/BHMA A156.9, B13292

Material substrate

- Made from brass

See finishes below

Available accessory items

- Security pin screws

Dimensions

- Body: 3/4" wide x 3" high x 3/4" deep
- Strike: 7/16" wide x 1-3/4" high x 7/8" deep



CL22 Ball catch

- Three-way catch with plate type strike.
- Ideal for smaller cabinet doors or panels.
- The strike slides between two stainless steel balls that are under spring tension. As the strike engages, the door is held tightly shut.
- Strike can enter body from either side or front.
- Spring tension is easily adjusted to suit field conditions.
- Body can be surface applied or mortised.
- Units packed with wood screws

Certifications

- Meets ANSI/BHMA A156.9, B13302

Material substrate

- Made from brass

See finishes below

Available accessory items

- Security pin screws

Dimensions

- Body: 1/2" wide x 2-3/16" high x 1/2" deep
- Strike: 3/8" wide x 1-3/8" high x 5/8" deep

CL21A and CL 22 Finishes

BHMA	Description	Substrate	Finish
605	Bright brass	Brass	US3
606	Satin brass	Brass	US4
612	Satin bronze	Brass	US10
625	Bright chrome	Brass	US26
626	Satin chrome	Brass	US26D

For other colors, consult factory.

Hinges & pivots

A

Pulls & plates

B

Flush bolts & coordinators

C

Latches, catches & bolts

D13

Stops

E

Exterior hardware

F

Miscellaneous hardware

G