



FS9 Floor stop & semi-automatic holder

- Semi-automatic floor-mounted holders accommodates with door to floor clearance of 1-1/2" or less
- Activate holder by flipping the engagement tongue forward. When door is opened, the hook (mounted on door) engages the tongue. To release, push firmly on door to disengage tongue
- Packed with fasteners for extra-heavy duty masonry and wood applications

Certifications

- Meets ANSI/BHMA 156.16, L11241

Material substrate

- Made from cast brass

Available accessory items

- Security pin screws
- Replaceable hook package

Dimensions

- Overall height: 3-1/2"
- Base dimensions: 2" wide x 3-1/2" long

Finishes

BHMA	Description	Substrate	Finish
605	Bright brass	Brass	US3
606	Satin brass	Brass	US4
612	Satin bronze	Brass	US10
613	Oil rubbed bronze	Brass	US10B
625	Bright chrome	Brass	US26
626	Satin chrome	Brass	US26D

For other colors, consult factory.



FS40 Floor stop & automatic holder

FS41

FS42

FS43

- Automatic door holders ideal for heavy-traffic situations that require a simple, fool-proof, Hold-open device
- Unit is activated automatically when door is opened. A firm pull on door releases the mechanism
- Strikes accommodate different door to floor clearances
- Model numbers are determined by strike/door-to-floor clearances
- Holder position on door is adjustable
- Packed with fasteners for heavy duty masonry and wood applications

Certifications

- Meets ANSI/BHMA 156.16, L11301

Material substrate

- Made from forged brass

Available accessory items

- Strike Packages

Dimensions

Door to floor clearance:

- FS40 1/2" or less
- FS41 9/16" to 1-1/16"
- FS42 1-1/8" to 1-9/16"
- FS43 1-5/8" to 2-1/16"

Holder dimensions:

- 3" wide x 3-11/16" high

Finishes

BHMA	Description	Substrate	Finish
605	Bright brass	Brass	US3
606	Satin brass	Brass	US4
612	Satin bronze	Brass	US10
613	Oil rubbed bronze	Brass	US10B
625	Bright chrome	Brass	US26
626	Satin chrome	Brass	US26D

For other colors, consult factory.

