

The global leader in  
door opening solutions

## Rockwood 550 - Lever Extension Flush Bolt



### Specifications:

**MATERIAL:**  
Brass

**FASTENERS:**  
8 ea. #8 x  $\frac{3}{4}$ " Flat Head Combo Screws

**FEATURES:**

- For Fire Rated Hollow Metal Swinging Doors measuring up to 4'w x 10'h rated up to and including 3 Hours
- $\frac{3}{4}$ " bolt throw,  $\frac{3}{4}$ " rod backset
- 12" rod length (center of face to bolt end - retracted)
- 1  $\frac{1}{2}$ " adjustable bolt head

**OPTIONS:**

- Other size rods available are 18", 24", 36", 48"
- Use #570 Dust Proof Strike to prevent dirt blocking bottom strike



### Available Finishes:

- US3/605
- US4/606
- US10/612
- US10B/613
- US10BE/613E
- US26/625
- US26D/626

**SIZE:**  
Face Plate: 1  $\frac{1}{4}$ " x 6  $\frac{3}{4}$ "  
Strike:  $\frac{15}{16}$ " x 2  $\frac{1}{4}$ "  
Guide: 1" x 2"

**WEIGHT:**  
1.7 lbs./2

**ANSI A156.16:**  
L04251