Architectural Door Accessories



The global leader in door opening solutions

Available

Finishes:

Rockwood 557 x 19BFB - Lever Extension Flush Bolt with Bottom Fire Bolt



• US26D/626

SIZE: Top Bolt: 1" x 6 ³/4" Bottom Bolt: Ø ¹³/16"

WEIGHT: 0.9 lbs.

Specifications:

MATERIAL:

- Flush Bolt Brass
- Bottom Fire Bolt Stainless Steel

FASTENERS:

7 ea. #8 x 3/4" Flat Head Combo Screws; 4 ea. #8-32 x 3/4" Flat Head Machine Screws; 4 ea. #8 Counter Sunk Washers

FEATURES:

- \bullet $^{3}\!/_{4}"$ bolt throw, $^{3}\!/_{4}"$ backset; door strength maintained by corner reinforcing plate
- When door is subjected to 230°F the plug and black plastic cover will melt allowing the bolt to project, locking the leaves together
- Bottom fire bolt eliminates need for floor prep
- Oversize fire bolt strike hole allows for slight door misalignment

300 Main Street Rockwood, Pennsylvania 15557 P: 800.458.2424 • F: 800.922.9212 www.rockwoodmfg.com • orders.rockwood@assaabloy.com

