

# Securitron® EPT Electrical Power Transfer

*Concealed, tamper resistant,  
flexible power and data transfer*



The Securitron EPT Electric Power Transfer provides concealed, secure power and data conduit between a frame and door, transmitting power to electrified locks, exit bars and more.

Its durable stamped steel housing and flexible spring steel conduit make the Securitron EPT suitable for most types of swinging doors with butt or continuous hinges or pivot hinges up to 3/4" offset. The Securitron EPT-SC accommodates swing-clear hinges and most pivot hinges.

## Features

### Standard Features

- Installs in the door and frame edges
- Flexible steel shield protects wire bundles up to 5/16" [8mm] thick
- Works with almost any type butt hinge, continuous hinges and some pivot hinges.
- Rounded mounting tabs
- MagnaCare® lifetime replacement, no-fault, no questions asked warranty

### Optional Features

- **EPT** for standard hinges and pivot hinges less than 3/4" [19mm] offset
- **EPTL** for extended length up to 5" center to center
- **EPT-SC** for swing-clear hinges or pivot hinges with larger offset; not for use with center pivot doors
- **EL** Models are ElectroLynx® compatible including 12–22 AWG wires, ElectroLynx connectors



*NOTE: Not every combination is possible.  
Please contact factory if you need a  
combination of features not listed above.*



MagnaCare  
Warranty



Windstorm  
Resistant

## Securitron EPT Electrical Power Transfer

## Specifications

## Certifications

- UL 10C Listed
- CAN4-S104 Listed
- UL 634 Listed (EL-EPT/ EL-EPTL)
- ULC/ORD-C634 (EL- EPT/EL-EPTL)
- ANSI/SDI-BHMA A250.13  
(+/- 60 PSF) Windstorm Listed

## Dimensions

- EPT Housing: 12-3/4" L x 7/8" W x 11/16" D  
[323.9mm L x 24.8mm W x 17.5mm D]
- EPTL Housing: 21-3/8" L x 7/8" W x 11/16" D  
[542.9mm L x 24.8mm W x 17.5mm D]
- Interior Flex Shield: 3/8" [9.5mm]

## Shipping Weight

- EPT: 0.75 lbs [0.34 kg]
- EPTL: 1.20 lbs [0.54 kg]
- EPT-SC: 1.25 lbs [0.57 kg]
- EL-EPT: 0.75 lbs [0.34 kg]
- EL-EPTL: 1.20 lbs [0.54 kg]
- EL-EPT-SC: 1.25 lbs [0.57 kg]

## How to Order

WIRE CONNECTORS	SHAPE	DOOR SWING/OPTIONS
<b>EL</b>	<b>- EPT</b>	<b>- SC</b>
(blank) No Connectors	EPT 10" Cord	(blank) Standard Swing SC Swing Clear / Pivots CSE 9 Wires
EL ElectroLynx® Connectors	EPTL 18" Cord*	(blank) Standard Swing Only

\*EPTL is only available in standard swing. No other options available.

## Dimensions

